



SPRING TYPE ACCESS PANEL

MAINTENANCE ACCESS COMPONENT

INTACT access panels are designed to provide convenient access to services installed above gypsum ceilings or behind drywall partitions. The panel integrates neatly with the surrounding surface and can be opened for inspection, maintenance and repair work.

PRODUCT SPECIFICATIONS

Product	Spring type with spring loaded handle
Frame Material	Extruded aluminium profile stipulated to BSSN 755-9-2008
Board thickness	12.50 mm
Door infill	Moisture-resistant gypsum board *
Color	RAL 9016
Opening mechanism	Spring catches
Finish	White powder coated finish
Size	Customisable to any size
Safety feature	Safety cable provided where applicable
Application	Ideal for ceilings and dry wall maintenance in residential, commercial & industrial buildings.

*Board infill can be matched to project specification.
Confirm the exact size and shape against the approved INTACT product schedule before use.



HIGH STRENGTH
& DURABILITY



CORROSION
RESISTANT



PRECISION
ENGINEERED



CONSISTENT QUALITY
& PERFORMANCE

AVAILABLE SIZES (mm)

- ✓ 200 × 200 mm
- ✓ 300 × 300 mm
- ✓ 400 × 400 mm
- ✓ 450 × 450 mm
- ✓ 500 × 500 mm
- ✓ 600 × 600 mm

*Other sizes available on request

OTHER FEATURES

- ✓ Inner & Outer frames are fixed by two spring loaded easy control handles.
- ✓ Removable door panels with safety features.
- ✓ High oxidation resistance
- ✓ Frame less appearance, rust proof, light weight, quick installation.